

Spring sleeves, style A

Item description/product images



Description

Material:


body, steel or 1.4303 (AISI 305 equivalent) stainless steel.
Spring, 1.4310 (AISI 301 equivalent) stainless steel wire.

Version:


body, steel nickel-plated, stainless steel bright.
Spring, bright.

Note:

Spring bodys are mainly used as indexing and positioning elements.



Drawings



Order No.	Main material	style	D1	L	L2	L by F1	L by F2	Spring force initial pressure F1 approx. N	Spring force final pressure F2 approx. N	Spring stiffness N/mm
K1277.112216	steel	A	2,2	16	7,8	12	10,5	2,2	3	0,53
K1277.112608	steel	A	2,6	8	3,8	6,5	5,2	1,1	2	0,7
K1277.113012	steel	A	3	12	6	9	8,7	6,2	6,8	2
K1277.113016	steel	A	3	16	8,5	13	10,7	4,8	8,4	1,6
K1277.113412	steel	A	3,4	12	6	9	7,8	5	7	1,69
K1277.113415	steel	A	3,4	15	7,3	12	8,2	5,9	13,3	1,95
K1277.114014	steel	A	4	14	8	12	9	5	12,3	2,45
K1277.115016	steel	A	5	16	8	13	10,4	8	15	2,7
K1277.123016	stainless steel	A	3	16	8	13	10,6	4,8	8,6	1,6